

# PORTA-C Inflatable Decontamination Shelter

Combined with the hose assembly from the PORTAflex 300/16e, this inflatable decontamination shelter is specifically designed for use where contaminated water needs to be contained. The replaceable inner lining has windows on two opposite sides to enable the decontamination process to be observed while openings on the other two sides enable personnel to walk through from the dirty to the clean area.





## Specifications

MATERIALS	
INFLATABLE FRAME	Neoprene coated polyester
LINER	Polyurethane coated polyester
SUMP	Nylon/butyl/nylon
PARTITION	Polyurethane coated polyester
WINDOWS	Velbex clear plastic
CARDAGE	Terylene or nylon
SERVICES	
VALVE - INFLATE ONLY	Rectus type 25 KS NW 7.8
VALVE - INFLATE/DEFLATE	Type A5
VALVE - RELIEF	Mirada 0.2 bar
MINIMUM FLOW RATES	75 liters/minute (20 US Gallons)
INLET SIZE COUPLING	2½" instantaneous
ASSEMBLY TIME	Less than 7 minutes
WEIGHTS and DIMENSIONS	
DIMENSIONS - Packed (WxDxH)	600 mm (23.6 in) x 500 mm (19.7 in) x 1200 mm (47.2 in)
DIMENSIONS - Assembled (WxDxH)	2200 mm (86.6 in) x 2200 mm (86.6 in) x 2900 mm (114.2 in)
WEIGHT	45 kg (99 lb)

**PORTA-C**

*Inflatable Decontamination Shelter*



**HUGHES**

**HUGHES-SAFETY.COM**

a Justrite® Group Company

Hughes North America Inc.  
 457 Campbell Street, Sarnia, Ontario N7T 2J1, Canada.  
 Email: [info@hughes-safety.com](mailto:info@hughes-safety.com)  
 Tel: +1 (866) 312 1652

Registered No. 0939240. VAT Registration No. 918 5005 32.  
 Hughes Safety Showers Ltd is a Justrite Group Company.

©2017 Hughes Safety Showers